

### 952-WATER-DRS · WATERDRS.COM

## Water Doctors Pro Logic Water Softener

#### 97% Efficiency and a Life Expectancy of Up to 25 Years

The Water Doctors Pro Logic Water Softener uses a patented microprocessor to adjust your water reserve based on previous needs, saving you money. Featuring adjustable cycles, up-flow regeneration, and a floating reserve to ensure a constant supply of soft water, the Pro Logic performs at the highest levels of efficiency.

Our exclusive soft water brining keeps internal parts vital to the proper operation of the system free from the wear and tear of hard water, and the easy-to-use LED display provides up-to-the-minute information on operational status and reserve capacity. With a 97% efficiency rating and a life expectancy of up to 25 years, the Pro Logic will provide worry and maintenance free soft water for years to come.

#### **Advanced Features**

- · High efficiency regeneration saves on salt & water usage
- · 365-day variable reserve accurately tracks and predicts daily water use
- Up-flow regeneration improves system performance & efficiency
- Soft water make-up brining adds years of trouble-free service
- High performance 1" control valve & 1" distributor ensures the highest possible flow rate throughout the home
- Twelve fully-programmable cycles provide the flexibility to treat a wide range of water problems
- Fully tested and engineered diagnostics
- Lifetime warranty on tanks; seven-year warranty on the control valve
- 97% efficiency (conversion of salt to sodium chloride)



#### **Diagnostics**

- · Counter-Current Flow Rate
- Peak Flow Rate (can be reset)
- Totalizer (can be reset)
- · Last Regeneration

#### **Model Numbers**

- WD-PRO-948 | 40.000
- WD-PRO-1054 | 60,000
- WD-PRO-1252 | 80,000









Water Doctors Pro Logic Specs			
	WD-PR0-948	WD-PR0-1054	WD-PRO-1252
Average Family Size	2-5 people	5-7 people	Large Property
Maximum Peak Flow Rate (LPM / USgal)	64 / 17	72 / 19	72 / 19
Maximum Continuous Flow Rate (LPM / USgal)	72 / 19	80 / 21	80 / 21
Minimum Temperature (°C / °F)	>0 / 32	>0 / 32	>0 / 32
Maximum Temperature (°C / °F)	<38 / 100	<38 /100	<38 / 100
Approximate Flush Volume (Liters / USgal)	132 / 35	170 / 50	185 / 55
Typical System Efficiency*	97%	97%	97%
Iron Removal (Ferrous)	1.0 ppm	1.5 ppm	2.0 ppm
Hardness Removal	>99.99%	>99.99%	>99.99%



# Water Doctors Water Treatment Company is a Minnesota-based national supplier of residential and commercial water filtration equipment.

Together with our parent company, HMI Water Specialists, Water Doctors has over 37 years of experience in the water treatment business. We have established a reputation as the industry leader in providing the highest quality equipment in this very specialized field. We employ a full staff of installation technicians, design engineers, and service professionals that bring 350 years of combined water service experience to the table.



This system has been tested for the treatment of water containing pentavalent arsenic (also known as As(V), As(+5), or arsenate) at concentrations of 0.050 mg/L or less. This system reduces pentavalent arsenic, but may not remove other forms of arsenic. This system is to be used on water supplies containing a detectable free chlorine residual or on water supplies that have been demonstrated to contain only pentavalent arsenic. Treatment with chloramines (combined chlorine) is not sufficient to ensure complete conversion of trivalent arsenic to pentavalent arsenic. Please see the Arsenic Facts section of the Performance Data Sheet for further information.

© Water Doctors Custom Engineered Water Systems. A consumer direct division of HMI Water Specialists. All rights reserved. 8201 Central Avenue NE, Minneapolis, MN 55432 952.928.3737 sales@waterdrs.com





